

MA30W/8

MA30W/8



MOUNTING INFORMATION

| | |
|------------------------|--------------|
| Overall Diameter | 310 mm (12") |
| Bolt Circle Diameter | 298 mm |
| Baffle cutout Diameter | 284 mm |
| Depth | 127 mm |
| Mounting Depth | 115 mm |
| Net Weight | 3,3 Kg |

SPECIFICATIONS

| | |
|---------------------|------------|
| Nominal Impedance | 8 Ohm |
| Output power | 300 W |
| Sensitivity (1W/1m) | 94 dB |
| Frequency Range | 40-4000 Hz |
| Voice Coil Diameter | 50 mm |
| Magnet | Ferrite |
| Magnet weight | 40 oz |
| Basket Material | Steel |

THIELE AND SMALL PARAMETERS

| | |
|------------|------------------------|
| Fo | 47.931 Hz |
| Re | 4.000 Ohm |
| Qes | 1,117 |
| Qms | 2,388 |
| Qts | 0,728 |
| Vas | 44,079 l |
| Sd | 530.93 cm ² |
| Mms | 88.126 gr |
| Bl | 10.962 TM |
| Kxm | 35.584 mH |
| Mmd | 81.092 mKg |
| Cms | 278.234 uM/N |
| Efficiency | 0.62% |