

MA13W/8

MA13W/8



MOUNTING INFORMATION

| | |
|------------------------|-------------|
| Overall Diameter | 130 mm (5") |
| Bolt Circle Diameter | 138 mm |
| Baffle cutout Diameter | 114 mm |
| Depth | 58 mm |
| Mounting Depth | 51 mm |
| Net Weight | 0.6 Kg |

SPECIFICATIONS

| | |
|---------------------|------------|
| Nominal Impedance | 8 Ohm |
| Output power | 80 W |
| Sensitivity (1W/1m) | 91 dB |
| Frequency Range | 80-6000 Hz |
| Voice Coil Diameter | 25 mm |
| Magnet | Ferrite |
| Magnet weight | 10 Oz |
| Basket Material | Steel |

THIELE AND SMALL PARAMETERS

| | |
|------------|----------------------|
| Fo | 95.349 Hz |
| Re | 4000 Ohm |
| Qes | 1,358 |
| Qms | 3,053 |
| Qts | 0,94 |
| Vas | 3,685 l |
| Sd | 75,43 m ² |
| Mms | 7.057 g |
| Bl | 3.955 Tm |
| Kxm | 11.203 mmH |
| Mmd | 6.680 mkg |
| Cms | 456.054 uM/N |
| Efficiency | 0.20% |