

CSX15



MOUNTING INFORMATION

| | |
|------------------------|--------|
| Overall Diameter | 394 mm |
| Bolt Circle Diameter | 374 mm |
| Baffle Cutout Diameter | 350 mm |
| Depth | 194 mm |
| Mounting depth | 180 mm |
| Net weight | 9,3 kg |

SPECIFICATION

| | |
|---------------------|------------|
| Nominal Impedance | 8 Ohm |
| RMS Power | 400 W |
| Max Power | 800 W |
| Sensitivity (1w/1m) | 97 dB |
| Frequency Range | 57-1800 Hz |
| Voice Coil Diameter | 75 mm |
| Magnet | Ferrite |
| Basket Material | Aluminum |
| Flux Density | 1.4 T |

THIELE AND SMALL PARAMETERS

| | |
|------|----------------------|
| Fs | 57 Hz |
| Re | 6.2 Ohm |
| Qes | 0,52 |
| Qms | 5,8 |
| Qts | 0,5 |
| Vas | 122 l |
| Sd | 1007 cm ² |
| Xmax | 3,5 mm |
| Mms | 87 gr |
| Bl | 18 Txm |
| Le | 29 mH |
| EBP | 109Hz |
| | |
| | |
| | |
| | |